*2 ELEVATION CERTIFICATE

O.M.B. No. 3067-007

Date Issued: 2-4-98 FEDERAL EMERGENCY MANAGEMENT AGENCY

Expires July 31, 1999

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are no required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on t	he following pages.
SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME ALBORT LUCORO	POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 6150 South SANDARIO Road Space	e #2 COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot and Block Numbers, etc.)	T /5 R /(\$ 9
TUCSOW	STATE ZIP CODE
SECTION B FLOOD INSURANCE RATE MAP (FIRM) I	NFORMATION
Provide the following from the proper FIRM (See Instructions):	
1. COMMUNITY NUMBER 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 040073 Z200 C Sept 6, 1989	5. FIRM ZONE 6. BASE FLOOD ELEVATION (in AO Zones, use depth)
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established the community's BFE. High Light Section	olished a BFE for this building site, indicate
SECTION C BUILDING ELEVATION INFORMA	ATION
 (a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor of level of the NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structhe selected diagram, is at an elevation of level of feet NGVD (or other FIRM (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is one) the highest grade adjacent to the building. If no flood depth number is available level) elevated in accordance with the community's floodplain management ordinance. 3. Indicate the elevation datum system used in determining the above reference level elevation Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevation under Comments on Page 2.) 	datum-see Section B, Item 7). diagram is 22. Seet above or feet above or below (check, is the building's lowest floor (reference er No Unknown ations: NGVD '29 Other (describe evations is different than that used on the FIRM and show the conversion
4. Elevation reference mark used appears on FIRM: \square Yes \overline{X} No (See Instructions on	Page 4)
5. The reference level elevation is based on: XX actual construction construction drawings is only valid if the building does not yet have the case this certificate will only be valid for the building during the course of construction. Will be required once construction is complete.)	reference level floor in place, in which
6. The elevation of the lowest grade immediately adjacent to the building is: Section B, Item 7).	feet NGVD (or other FIRM datum-see
SECTION D COMMUNITY INFORMATIO	N
If the community official responsible for verifying building elevations specifies that the resis not the "lowest floor" as defined in the community's floodplain management ordinance floor" as defined by the ordinance is:	e, the elevation of the building's "lowest

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE), V1–V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide fleodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.


I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

Al	but Luc	~~		2 . 1	
CERTIFIER'S NAME	- B - 54		LICENSE NUMBER (or A	Sacel	
TITLE	UNEL	COMPANY	Y NAME	7210n	
4000500				front c	
ADDRESS 7/	LS DARFORD	- U JAUE	TUCSON	7320 back	- B 5-74
SIGNATURE	1	~~~	DATE	I changed it felt	

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS:

Pima County Floodplain and Erosion Hazard Management Ordinance 1994-FC2 in Article XI requires the bottom of the structural frame of a manufactured home to be a minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350.



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.