## **ELEVATION CERTIFICATE**

PCFC JAN19700pm **Q:B.B**. No. 3067-0077

Expires July 31, 1999

FEDERAL EMERGENCY MANAGEMENT AGENCY issued: Date NATIONAL FLOOD INSURANCE PROGRAM

Type 1 MHDAG ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages. FOR INSURANCE COMPANY USE PROPERTY INFORMATION SECTION A POLICY NUMBER ING OWNER'S NAME COMPANY NAIC NUMBER Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER OTHER DESCRIPTION (Lot and Block Numbers, etc.) R STATE CITY SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 5. FIRM ZONE 6. BASE FLOOD ELEVATION 4. DATE OF FIRM INDEX 2. PANEL NUMBER 3. SUFFIX 1. COMMUNITY NUMBER (in AO Zones, use depth) FOO'1 040073 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate feet NGVD (or other FIRM datum-see Section B, Item 7) the community's BFE SECTION C BUILDING ELEVATION INFORMATION 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level \_ 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation <del>☐ feet NGVD (or other FIRM datum—see Section B, Item 7):</del> (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from ifeet NGVD (or other FIRM datum-see Section B, Item 7): the selected diagram, is at an elevation of (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is \_\_\_\_\_ feet above \_\_\_ or below [ (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is 15 feet above X or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 

Yes 

No 

Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 - Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Tyes X No (See Instructions on Page 4) 5. The reference level elevation is based on: XX actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: Section B, Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest <del>∫ feet NGVD (or other FIRM datum-see Section B, Item 7).</del> floor" as defined by the ordinance is: 2. Date of the start of construction or substantial improvement SEE REVERSE SIDE FOR CONTINUATION

## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide fleedplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code. Section 1001

	The statement may be pu	misnable by fine or imprisonment	t under 18 U.S. Code, Section 1001.	oie.
CERTIFIER'S NAM	-N ( I dian	:	/	· •
OWW.		. LICENSE	NUMBER (or Affix Seal)	
ADDRESS / 17	S. SilversTA	COMPANY NAME L DUCSON		- Firm
SIGNATURE	en Oga	CÎTY //	15/00 408-2408 ATP PHONE	ZIP
Copies should	be made of this Certificate for:	1) community official, 2) insur	ance agent/company, and 3) building	OWnor
COMMENTS:	Article XI requires the borminimum of one foot above county requires the manusone half feet above the base flow elevation certificate is to be seven days of placement of	and Erosion Hazard Manage ttom of the structural frame we the base flood elevation. factured home floor reference ttom of the structural frame bood elevation as listed in item are certified in Sections C and fithe manufactured by	ement Ordinance 1994-FC2 in of a manufactured home to be a For "A" or "AO" Zones Pima ce level to be a minimum of one elevation which equals two and m 6 of Section B of this form. The	and one
ZO	ON SLAB A V ONES ZONES	WITH BASEMENT  A ZONES	ON PILES, PIERS, OR COLUMNS  A  ZONES ZONES	

SLAB

A

ZONES

A

ZONES

ZONES

ZONES

A

ZONES

ZONES

REFERENCE
LEVEL

REFERENCE
RADACENT
GRADE

ADJACENT
GRADE

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.