FPUP 99-659E-A

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 1999 Type 1 MHDAG

Date Issued:

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages.

					-
	SECTION A PRO	OPERTY INFO	RMATION		FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME	le				POLICY NUMBER
STREET ADDRESS (Including Ap		Number) OR P.O. R	OUTE AND BOX NUMBER		COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot and E 5 220' of NW/4		(C W 40' Fo	RRd. 3.13AC.	T /5	R//E s 03
CITY	•			STATE	ZIP CODE 85743
Tueson	SECTION B FL	OOD INSURA	NCE RATE MAP (FIRM)	INFORMATION	· · · · · · · · · · · · · · · · · · ·
Provide the following from the					· · · · · · · · · · · · · · · · · · ·
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION
040073	2200	K	2-8-99	Α	(in AO Zones, use depth)
7. Indicate the elevation dat 8. For Zones A or V, where the community's BFE:	no BFE is provided o	n the FIRM, a n	ase Flood Elevations (BFE ad the community has esta FIRM datum—see Section	ablished a BFE-f	Other (describe on back) or this building site, indicate
	SECTION	ON C BUILDI	NG ELEVATION INFORM	IATION	
of	t NGVD (or other FIF VE, and V (with BFE) is at an elevation of EBFE). The floor used the highest grade action used as the referadjacent to the build redance with the communication system used in die 2). (NOTE: If the B, Item 7], then converts on Page 2.)	The bottom of th	Section B, Item 7): of the lowest horizontal structure feet NGVD (or other FIR nee level from the selecte building. In the selected diagram is didepth number is available ain management ordinant above reference level elem used in measuring the ensity the datum system uses to the datum system uses the datum system uses to the datum system uses the datum system system uses the datum system	d diagram is different in the FIRM is diagram is different in the FIRM is diagram is different in the FIRM is diagram in the FIRM is diagram in the FIRM is diagram in the firm in the	ection B, Item 7): Solution B, Item 7): So
5. The reference level eleval (NOTE: Use of construct case this certificate will or will be required once con.) 6. The elevation of the lower Section B; Item 7).	ation is based on: XX tion drawings is only nly be valid for the bu struction is complete.	actual construiction actual construiction actual construite the construint construint actual construint actual construint	uction construction diding does not yet have the course of construction.	rawings e reference leve A post-construc	l floor in place, in which tion Elevation Certificate (or other FIRM datum-see
<u> </u>	s	ECTION D CO	OMMUNITY INFORMATION	ON ,	
If the community official is not the "lowest floor" as defined by the case. Date of the start of const.	responsible for verifying self-ined in the commercial desiration of the co	ng building ele nunity's floodpl	vations specifies that the lain management ordinan NGVD (or other FIRM date	reference level in	

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

COMPANY NAME. DDRESS 42.75 N. O. A. CITY	ABL MOD	ile Movers (C. Kevin Wil)	LICE	NSE NUMBER (or Affix Seal)		
DATE TO STATE TO STAT	TLE	C. Tavib will		247 I-10C		
STATE REPRESENTED AND AND STATE REPRESENCE TO STATE REPRESENCE TO STATE REPRESENTED AND STATE REPRESENCE TO STATE REPRESENCE T	000500		SOM ANT NAME			
DATE 2 4 -99 PHONE 888-2965 Depletes should be made of this Certificate for: 1) community official, 2) Insurance agent/company, and 3) building owner. DIMMENTS: Pima County Floodplain and Erosion Hazard Management Ordinance 1994-FC2 in Article XI requires the bottom of the structural frame of a manufactured home to be a minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. Note 1		0/ 1	CITY			
DATE 2 4 99 PHONE YES - 2965 PRISE - 2965	GNATURE	Plyn Ave	Tuesan			ZIF
Pima County Floodplain and Erosion Hazard Management Ordinance 1994-FC2 in Article XI requires the bottom of the structural frame of a manufactured home to be a minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB JOHN BLES, DRESDIES JOHN BLES, DRESDIES JOHN BLANCENT GREEFRENCE LEVEL JOHN BLANCENT GRANCEST ADJACENT ADJACEN		Kuni flatto		DATE	HONE	
Article XI requires the bottom of the structural frame of a manufactured home to be a minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB ZONES ZONES ZONES ABJETITION REFERENCE LEVEL ADJACENT ADJACE	pies should	be made of this Cortificate for the	·			5
Article XI requires the bottom of the structural frame of a manufactured home to be a minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB ZONES ZONES ZONES ABJETITION REFERENCE LEVEL ADJACENT ADJACE			community official, 2) is	nsurance agent/company	, and 3) building o	wner.
minimum of one foot above the base flood elevation. For "A" or "AO" Zones Pima County requires the manufactured home floor reference level to be a minimum of one and one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON PILES, PIERS, OR COLUMNIS ZONES ABASEMENT		Fima County Floodplain and	d Frosion Hazard Ma	100		
County requires the manufactured home floor reference level to be a minimum of one and one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB ON PILES, PIERS, OR COLUMNS ADAGENT ORADE PEFERENCE LEVEL ADAGENT ORADE The diagrams above illustrate the points at which the elevations should be measured in Azones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.	Z.(10.					,
one half feet above the bottom of the structural frame elevation which equals two and one half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB JONES JONE						
half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB JONES JONE		County requires the manufac	tured home floor	on. ror "A" or "AO"	Zones Pima	
half feet above the base flood elevation as listed in item 6 of Section B of this form. This elevation certificate is to be certified in Sections C and E. A copy is to be returned within seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB WITH BASEMENT ON PILES. PIERS OR COLUMNS ZONES ZONES ZONES ZONES ZONES ZONES ZONES ZONES ZONES LEVEL SONES ZONES PAGE FLOOR SELEVATION ELEVATION LEVEL DAMAGENT ORACE LEVEL		one half feet above the hotto	m of the startered of	rence level to be a mi	nimum of one a	nd
elevation certificate is to be certified in Section B of Section B of this form. This seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB ZONES ZONES ZONES ON PILES, PIERS, OR COLLUMNS ADJACENT LEVEL ADJACENT COMADE The diagrams above illustrate the points at which the elevations should be measured in AZones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.						
seven days of placement of the manufactured home, to Pima County Floodplain Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740- 6350. ON SLAB JONES JONE						
Management Section, 201 N. Stone Ave., 4th Floor, Tucson, AZ 85701. Phone 740-6350. ON SLAB JONES						in
ON SLAB ON PILES, PIERRENCE LEVEL ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in AZones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.						
ON SLAB A ZONES REFERENCE LEVEL REFERENCE REFERENCE REFERENCE REFERENCE REFERENCE REFERENCE REFERENCE REFERENCE REFERENCE REF		6350	. Stone Ave., 4 th Floor	, Tucson, AZ 85701.	Phone 740-	
SLAB A ZONES Z		0330.				
ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. BASEMENT ADJACENT GRADE PIERS, OR COLUMNS ADJACENT ADJACENT GRADE REFERENCE LEVEL ADJACENT GRADE ADJACENT GRADE ADJACENT GRADE LEVEL ADJACENT GRADE		ON				
ZONES REFERENCE LEVEL REFERENCE LEVEL ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor		SLAB		#3 PIERS O	PILES,	
PEFERENCE LEVEL BASE FLOCO ELEVATION REFERENCE ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.	Z	A V	A	/	- COLDMAS	
BASE PLOOD ELEVATION REFERENCE LEVEL ADJACENT GRADE REFERENCE LEVEL ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.		ZONES	ZONES		ZONES TA	
BASE FLOCO ELEVATION REFERENCE ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in Azones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.	PEFERENCE LEVEL					_ \
BASE FLOCO ELEVATION REFERENCE ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.			FLOO			
The diagrams above illustrate the points at which the elevations should be measured in Azones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~				4	· ·
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.	BASE					~
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.				T 1 19	(\\ FLOO	10
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.		LEVEL GRADE		- / M	ELEVAT	TON
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.					4//	
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.		•	•			/
The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.				\		
and A Zones should be measured at the top of the reference level floor	•			/ ********	M) ADJACE	ENT :
and A Zones should be measured at the top of the reference level floor	•					_
Elevations for all V Zamania and the measured at the top of the reference level floor.	The diagram	s above illustrate the points at which	the elevations of the			/
S PENNING HOS BOOK AND	The diagrams	s above illustrate the points at which	the elevations should be	measured in A Zones and	V Zones.	
		all A Zones should be measured at	the top of the reference is	evel floor		